



MINA PLANAR MAGNETIC T-300-15-1.3-20W-FLBK

**SINGLE ENDED DCM FLY BACK TRANSFORMER TOPOLOGY
NOMINAL INPUT VOLTAGE 300 VOLTS
NOMINAL OUTPUT VOLTAGE 15VOLTS**

PLANAR TRANSFORMER SPECIFICATION

One of the most significant components that goes into a power supply is the power transformer, Mina can provide you with our unique planar magnetic for your next design or retrofit your existing product with our planar transformer and inductor. With our fifteen years of research and development using new material we can produce new planar constructions thereby producing a highly efficient planar transformer that is lower in cost compared to conventional wire or copper wound transformers across all switch mode power conversion topology and power levels. These planar transformers are available for all switch mode topologies and they provide shielding to minimize or eliminate radiated EMI and RFI. They are suitable for Zero Voltage Switching (ZVS), Zero Current Switching (ZCS) or hard switching application. This is a Fly Back topology planar transformer. If pins 6-9 are shorted and connected to chassis ground, radiated EMI will be minimized or eliminated. They are suitable for Zero Voltage Switching (ZVS), Zero Current Switching (ZCS) or hard switching application. They also meet military, aerospace, industrial and telecommunication applications requirements. If you do not find a transformer suitable for your applications, we will be glad to provide customer one. Please let us know what you want by either sending us e-mail or completing the form on our website "What I Want". We will respond immediately.

ELECTRICAL SPECIFICATION¹

PARAMETER	UNITS
Input Voltage Range	100 – 400 VDC
Input Current Peak To Peak	1.1 Amps Maximum (Low Line) ²
Nominal Output Voltage	15 Volts
Output Voltage Range	10 Volts - 18 Volts
Output Current	1.33 Amps Maximum
Primary Turns	40 Turns
Secondary Turns	4 Turns
Auxiliary output voltage	15 Volts
Auxiliary turns	4 Turns
Flux Density Peak to Peak	150 mT Maximum
Switching Frequency	200 kHz Minimum
Maximum Duty Cycle	45.0 %
Maximum Temperature Rise Hot Spot	10 ⁰ C
Efficiency At Maximum Power	99.5%
Isolation Voltage Primary to Core	1500 VDC
Isolation Voltage Primary to Secondary	2500 VDC
Isolation Voltage Secondary To Core	1500 VDC
Primary DC Resistance	0.5Ω
Secondary DC Resistance	0.5 Ω

1. See 100 W Class Mechanical Specification And Electrical Winding Orientation Data Sheet

**www.minamag.com Phone: 972-699-9976 Fax: 972-699-9977 Sales@minamag
Rev1 March 3rd 2010**